



Designed and manufactured at the Graphite Design Japan factory headquarters, the **Tour AD F-Series** Fairway shafts are available in 55g R2, R1 and S Flex, 65g SR (Stiff Regular) S and X flex, 75g S and X flex and 85g S and X flex.

The **Tour AD F-Series** Fairway shafts are designed with a softer tip and stiffer butt profile and feature a Low Kick Point for higher launch conditions into the air and mid-ball spin. Manufactured under the same tight tolerances and with premium, aerospace quality 40t carbon-fiber materials, the **Tour AD F-Series** of shafts fall directly in line with all of the other high quality Graphite Design shafts as a complementing Fairway wood shaft.

Should you be searching for a new Fairway shaft that is designed to provide maximum distance and extra forgiveness off the fairways, then a new **Tour AD F-Series** Fairway graphite shaft may be the answer to what you are looking for in a high performance golf shaft for your Fairway metal-woods.

MSRP \$300  
 PROSCHOICEGOLFSHAFTS.COM  
 760-476-9598



### SHAFT SPECIFICATIONS

Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
Tour AD F-55 R2	ADFW5-R2	Lite/Senior	44.0"	59.0	.335"	3.0"	.598"	5.0°	Low
Tour AD F-55 R1	ADFW5-R1	Regular	44.0"	60.0	.335"	3.0"	.598"	5.0°	Low
Tour AD F-55 S	ADFW5-S	Stiff	44.0"	60.0	.335"	3.0"	.602"	5.0°	Low
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
Tour AD F-65 SR	ADFW6-SR	Stiff Regular	44.0"	68.0	.335"	3.0"	.604"	3.3°	Low
Tour AD F-65 S	ADFW6-S	Stiff	44.0"	68.0	.335"	3.0"	.604"	3.3°	Low
Tour AD F-65 X	ADFW6-X	X-Stiff	44.0"	70.0	.335"	3.0"	.606"	3.3°	Low
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
Tour AD F-75 S	ADFW7-S	Stiff	44.0"	77.0	.335"	3.0"	.598"	3.2°	Low
Tour AD F-75 X	ADFW7-X	X-Stiff	44.0"	79.0	.335"	3.0"	.602"	3.2°	Low
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
Tour AD F-85 S	ADFW8-S	Stiff	44.0"	89.0	.335"	3.0"	.602"	2.8°	Low
Tour AD F-85 X	ADFW8-X	X-Stiff	44.0"	91.0	.335"	3.0"	.604"	2.8°	Low

Tip Trimming for Standard Bore Heads: #3 wood: .5", #5 wood or greater: 1.0", then Butt Cut to desired club length after assembly.



PROSCHOICEGOLFSHAFTS.COM