



The Tour AD GT wood shaft model was designed and is manufactured exclusively at the Graphite Design factory headquarters in Japan. The Tour AD GT is available in 50g R2(Lite), R1(Regular) and S flex, 60g SR(Stiff Regular), S and X flex, 70g S and X flex and 80g S and X flex.

The **Tour AD GT** design is an overall softer tip and stiffer butt shaft yet if features an overall slightly stiffer bend profile than its brother, the Tour AD DJ, resulting in a higher kick point that produces a MID trajectory while maintaining optimal spin control. Like all of the premium Tour AD wood shafts, the **Tour AD GT** utilizes premium, aerospace quality 50t carbon-fiber and the 1st generation of Toray Nano-alloy material technology known as "DI Technology" for amazing feel and improved performance in Accuracy and Distance.

Revolutionary technology, design and the most advanced materials are trademarks in all Graphite Design shafts, making them the highest quality premium golf shafts on the market today. Validating the company's "Tour AD" logo, all of Graphite Design's PGA Tour-proven shafts are specifically designed to promote a gain in <u>Accuracy and </u>Distance.

> MSRP \$500 PROSCHOICEGOLFSHAFTS.COM 760-476-9598



Shaft Type Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD GT 5 R2 ADGT5-R2	Lite/Senior	46″	55	.335"	3.0"	.595"	4.3	MID
TOUR AD GT 5 R1 ADGT5-R1	Regular	46″	55.5	.335"	3.0"	.596"	4.3	MID
TOUR AD GT 5 S ADGT5-S	Stiff	46″	57	.335"	3.0"	.598"	4.3	MID
Shaft Type Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD GT 6 SR ADGT6-SR	Stiff Regular	46″	64.5	.335"	3.0"	.596"	3.1	MID
TOUR AD GT 6 S ADGT6-S	Stiff	46″	65	.335"	3.0"	.598"	3.1	MID
TOUR AD GT 6 X ADGT6-X	X-Stiff	46″	67.5	.335"	3.0"	.600"	3.1	MID
Shaft Type Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD GT 7 S ADGT7-S	Stiff	46″	74.5	.335"	3.0"	.600"	2.9	MID
TOUR AD GT 7 X ADGT7-X	X-Stiff	46″	76	.335"	3.0"	.602"	2.9	MID
Shaft Type Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD GT 8 S ADGT8-S	Stiff	46″	86.5	.335"	3.0"	.602"	2.6	MID
	X-Stiff	46″	88	.335"	3.0"	.604"	2.6	MID
IOUR AD GI 8 X ADGI8-X							t Cut to de	esired
TOUR AD GT 8 S ADGT8-S   TOUR AD GT 8 X ADGT8-X   Tip Trimming for Standard Bore He club length after assembly.	ads: Driver: 0.(	)", #3 wo	od: .5″, 7	≠5 Wood o	r greater 1.u	, inen bui		

SHAFT SPECIFICATIONS

## **PROSCHOICEGOLFSHAFTS.COM**