



Tour AD MJ

Designed and manufactured at the Graphite Design Japan factory headquarters, the **Tour AD MJ** wood shaft is available in 50g R2, R1 and S flex, 60g SR, S and X flex, 70g S and X flex and 80g S and X flex.

The **Tour AD MJ** utilizes premium, aerospace quality 50t carbon-fiber materials to provide the best performing shaft available. Designed with a softer tip and stiffer mid to butt section to promote a higher launch condition and low/mid spin, the **Tour AD MJ** also utilizes the 3rd generation version of the Toray Nano-alloy material technology known as "**DI Technology**" in the tip section of the shaft for additional shaft stability, exceptional feel and precise ball control. Try the new **Tour AD MJ**, it might just make a **MAJOR** impact on your game today.

MSRP \$500
 PROSCHOICEGOLFSHAFTS.COM
 760-476-9598



SHAFT SPECIFICATIONS

| Shaft Type | Part Number | Flex | Length | Wt | Tip OD | Tip Para. | Butt OD | Torque | Kick pt |
|-----------------|-------------|---------------|--------|-------|--------|-----------|---------|--------|---------|
| TOUR AD MJ 5 R2 | ADMJ5-R2 | Lite/Senior | 46" | 53g | .335" | 3.0" | .596" | 4.7 | LOW/MID |
| TOUR AD MJ 5 R1 | ADMJ5-R1 | Regular | 46" | 53.5g | .335" | 3.0" | .596" | 4.7 | LOW/MID |
| TOUR AD MJ 5 S | ADMJ5-S | Stiff | 46" | 55g | .335" | 3.0" | .598" | 4.7 | LOW/MID |
| Shaft Type | Part Number | Flex | Length | Wt | Tip OD | Tip Para. | Butt OD | Torque | Kick pt |
| TOUR AD MJ 6 SR | ADMJ6-SR | Stiff Regular | 46" | 61g | .335" | 3.0" | .596" | 3.4 | LOW/MID |
| TOUR AD MJ 6 S | ADMJ6-S | Stiff | 46" | 62.5g | .335" | 3.0" | .598" | 3.4 | LOW/MID |
| TOUR AD MJ 6 X | ADMJ6-X | X-Stiff | 46" | 64g | .335" | 3.0" | .600" | 3.4 | LOW/MID |
| Shaft Type | Part Number | Flex | Length | Wt | Tip OD | Tip Para. | Butt OD | Torque | Kick pt |
| TOUR AD MJ 7 S | ADMJ7-S | Stiff | 46" | 71g | .335" | 3.0" | .600" | 3.2 | LOW/MID |
| TOUR AD MJ 7 X | ADMJ7-X | X-Stiff | 46" | 72.5g | .335" | 3.0" | .602" | 3.2 | LOW/MID |
| Shaft Type | Part Number | Flex | Length | Wt | Tip OD | Tip Para. | Butt OD | Torque | Kick pt |
| TOUR AD MJ 8 S | ADMJ8-S | Stiff | 46" | 84.5g | .335" | 3.0" | .602" | 2.8 | LOW/MID |
| TOUR AD MJ 8 X | ADMJ8-X | X-Stiff | 46" | 86g | .335" | 3.0" | .604" | 2.8 | LOW/MID |

Tip Trimming for Standard Bore Heads: Driver: 0.0", #3 wood: .5", #5 Wood or greater 1.0", then Butt Cut to desired club length after assembly.



PROSCHOICEGOLFSHAFTS.COM