



Designed and manufactured at the Graphite Design Japan factory headquarters, the **Tour AD TP** wood shaft is available in 40g R2, R1 and S flex, 50g R2, R1 and S flex, 60g SR, S, X and TX flex, 70g S, X and TX flex and 80g S and X flex.

Designed around new tooling, the **Tour AD TP** utilizes a technology called **Fast Taper Technology** or "FTT". This technology incorporates a faster taper rate from the lower mid-section to the tip of the shaft than previous Tour AD wood shaft models. The **Fast Taper Technology** provides the overall feeling of greater club head control at impact and an increase in club head speed through the swing.

The new **Tour AD TP** shaft has a medium stiffness starting at the handle thru the mid-section of the shaft and a stiff tip profile to promote a mid to mid/high launch condition and low spin. The new **Tour AD TP** utilizes premium, 50t carbon fiber materials as well as the ultra-high tensile strength TORAYCA® T1100G carbon-fiber with NANOALLOY® technology in the tip section for additional shaft stability, exceptional feel and precise ball control.

Make a change in your Driver or Fairway metal wood today to the same shaft that the professionals use, the new "Tour Proven" **Tour AD TP** model of premium Graphite Design graphite golf shafts with **FTT - Fast Taper Technology**.

MSRP \$500
 PROSCHOICEGOLFSHAFTS.COM
 760-476-9598



SHAFT SPECIFICATIONS

Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD TP 4 R2	ADTP4-R2	Lite/Senior	46"	46.0	.335"	3.0"	.594"	5.7	MID
TOUR AD TP 4 R1	ADTP4-R1	Regular	46"	47.0	.335"	3.0"	.594"	5.7	MID
TOUR AD TP 4 S	ADTP4-S	Stiff	46"	48.0	.335"	3.0"	.596"	5.7	MID
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD TP 5 R2	ADTP5-R2	Lite/Senior	46"	54.0	.335"	3.0"	.596"	4.4	MID
TOUR AD TP 5 R1	ADTP5-R1	Regular	46"	56.0	.335"	3.0"	.598"	4.4	MID
TOUR AD TP 5 S	ADTP5-S	Stiff	46"	57.0	.335"	3.0"	.600"	4.4	MID
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD TP 6 SR	ADTP6-SR	Stiff Regular	46"	64.0	.335"	3.0"	.596"	3.2	MID
TOUR AD TP 6 S	ADTP6-S	Stiff	46"	65.0	.335"	3.0"	.598"	3.2	MID
TOUR AD TP 6 X	ADTP6-X	X-Stiff	46"	67.0	.335"	3.0"	.600"	3.2	MID
TOUR AD TP 6 TX	ADTP6-TX	Tour X-Stiff	46"	68.0 g	.335"	3.0"	.602"	3.2	MID
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD TP 7 S	ADTP7-S	Stiff	46"	73.0	.335"	3.0"	.600"	3.0	MID
TOUR AD TP 7 X	ADTP7-X	X-Stiff	46"	75.0	.335"	3.0"	.602"	3.0	MID
TOUR AD TP 7 TX	ADTP7-TX	Tour X-Stiff	46"	76.0 g	.335"	3.0"	.604"	3.0	MID
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD TP 8 S	ADTP8-S	Stiff	46"	85.0	.335"	3.0"	.600"	2.6	MID
TOUR AD TP 8 X	ADTP8-X	X-Stiff	46"	87.0	.335"	3.0"	.602"	2.6	MID

Tip Trimming for Standard Bore Heads: Driver: 0.0", #3 wood: .5", #5 Wood or greater 1.0", then Butt Cut to desired club length after assembly.



PROSCHOICEGOLFSHAFTS.COM