



Brand new for the 2019 season, Graphite Design introduces the latest in the Tour AD premium line of hybrid golf shafts, the **Graphite Design Tour AD IZ – "Into the Zone" Hybrid**. Designed and manufactured at the Graphite Design Japan factory headquarters, the new **Tour AD IZ** hybrid shaft are available in 65g R2 (Lite) and R1 (Regular) flex, 75g R and S flex, 85g R, S and X flex and 95g S and X.

The **Tour AD IZ Hybrid**, like all of the premium Tour AD shafts, utilizes premium, aerospace quality carbon-fiber materials in order to deliver the best feeling and performing shaft available to golfers.

The **Tour AD IZ 65g and 75g** hybrid shaft has a medium stiffness starting at the handle, and firm center section and a firm tip profile to promote a mid/high launch angle and mid ball spin rates.

The **Tour AD IZ 85g and 95g** hybrid shaft has a firm stiffness starting at the handle, and firm center section and a stiff tip profile to promote a mid-launch angle and lower ball spin rates.

Reach out to your local Golf Club Fitting professional and ask about how to get your hybrid or Driving Iron club "Into the Zone" using the new Tour AD IZ Hybrid model of premium Graphite Design graphite golf shafts.

MSRP \$290 PROSCHOICEGOLFSHAFTS.COM

760-476-9598



| SHAFT SPECIFICATIONS   |  |                             |                         |                   |                     |                      |                |                   |                      |
|--|--|-----------------------------|-------------------------|-------------------|---------------------|----------------------|----------------|-------------------|----------------------|
| Shaft Type   | Part Number                            | Flex                        | Length                  | Wt                | Tip OD              | Tip Para.            | Butt OD        | Torque            | Kick pt              |
| Tour AD IZ Hybrid 65 R2  | ADIZHB65-R2                            | R2/Lite                     | 42.0"                   | 65g               | .370"               | 3.0"                 | .600"          | 3.5               | LOW/MID              |
| Tour AD IZ Hybrid 65 R1  | ADIZHB65-R1                            | R1/Regular                  | 42.0"                   | 65g               | .370"               | 3.0"                 | .600"          | 3.5               | LOW/MID              |
| Shaft Type   | Part Number                            | Flex                        | Length                  | Wt                | Tip OD              | Tip Para.            | Butt OD        | Torque            | Kick pt              |
| Tour AD IZ Hybrid 75 Regular   | ADIZHB75-R                             | Regular                     | 42.0"                   | 76g               | .370"               | 3.0"                 | .598"          | 3.1               | LOW/MID              |
| Tour AD IZ Hybrid 75 Stiff   | ADIZHB75-S                             | Stiff                       | 42.0"                   | 78g               | .370"               | 3.0"                 | .598"          | 3.1               | MID                  |
|  |  |                             |                         |                   |                     |                      |                |                   |                      |
| Shaft Type   | Part Number                            | Flex                        | Length                  | Wt                | Tip OD              | Tip Para.            | Butt OD        | Torque            | Kick pt              |
| Shaft Type  Tour AD IZ Hybrid 85 Regular   | Part Number ADIZHB85-R                 | <b>Flex</b><br>Regular      | Length<br>42.0"         | Wt<br>84g         | <b>Tip OD</b> .370" | Tip Para.            | .602"          | Torque<br>2.4     | Kick pt<br>MID       |
| ,,   |  |                             |                         |                   |                     |                      |                |                   | •                    |
| Tour AD IZ Hybrid 85 Regular   | ADIZHB85-R                             | Regular                     | 42.0"                   | 84g               | .370"               | 3.0"                 | .602"          | 2.4               | MID                  |
| Tour AD IZ Hybrid 85 Regular  Tour AD IZ Hybrid 85 Stiff                               | ADIZHB85-R<br>ADIZHB85-S               | Regular<br>Stiff            | 42.0"<br>42.0"          | 84g<br>86g        | .370"               | 3.0"                 | .602"          | 2.4               | MID/HIGH             |
| Tour AD IZ Hybrid 85 Regular  Tour AD IZ Hybrid 85 Stiff  Tour AD IZ Hybrid 85 X-Stiff | ADIZHB85-R<br>ADIZHB85-S<br>ADIZHB85-X | Regular<br>Stiff<br>X-Stiff | 42.0"<br>42.0"<br>42.0" | 84g<br>86g<br>88g | .370"<br>.370"      | 3.0"<br>3.0"<br>3.0" | .602"<br>.602" | 2.4<br>2.4<br>2.4 | MID/HIGH<br>MID/HIGH |

Tip Trimming for Standard Bore Heads: 15-18° loft: 0.0", 19-22° loft: 0.5", 23° of greater loft: 1.0", then butt cut to desired club length after assembly.



PROSCHOICEGOLFSHAFTS.COM