



The **Graphite Design Tour AD VR** – designed to “Vanquish all Rivals” was designed and is manufactured at the Graphite Design Japan factory headquarters. The **Tour AD VR** wood shafts are dark blue with white and silver accents and are finished with a matte clear coat and are available in 40g R2, R1 and S flex, 50g R2, R1, S and X flex, 60g SR, S and X flex, 70g S and X flex and 80g S and X flex.

The **Tour AD VR**, like the other premium Tour AD wood shafts, utilizes premium, aerospace quality 50t carbon-fiber materials and it has a slightly higher balance point than the other current Tour AD wood shaft profiles. The Tour AD VR shaft also utilizes **FTT -Fast Taper Technology**, which incorporates a faster taper rate from the grip to the lower mid-section of the shaft, providing the overall feeling of greater club head control at impact and an increase in club head speed.

The **Tour AD VR** shaft profile is firm to stiff starting at the handle, medium/firm in the center section and has a firm tip to promote a mid/high launch angle and low ball spin rates. The **Tour AD VR** also utilizes TORAYCA® T1100G carbon-fiber pre-preg with NANOALLOY® technology in the tip section of the shaft for additional shaft stability, exceptional feel and precise ball control.

See a Graphite Design authorized Golf Club Fitting professional and come to the tee box ready with your new **Tour AD VR** wood shaft and “Vanquish all Rivals” from tee to green.

MSRP \$500
 PROSCHOICEGOLFSHAFTS.COM
 760-476-9598



SHAFT SPECIFICATIONS

Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD VR 4 R2	ADVR4-R2	Lite/Senior	46"	46	.335"	3.0"	.596"	5.7°	Mid
TOUR AD VR 4 R1	ADVR4-R1	Regular	46"	47	.335"	3.0"	.596"	5.6°	Mid
TOUR AD VR 4 S	ADVR4-S	Stiff	46"	47	.335"	3.0"	.596"	5.6°	Mid
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD VR 5 R2	ADVR5-R2	Lite/Senior	46"	54	.335"	3.0"	.598"	4.5°	Mid
TOUR AD VR 5 R1	ADVR5-R1	Regular	46"	56	.335"	3.0"	.600"	4.5°	Mid
TOUR AD VR 5 S	ADVR5-S	Stiff	46"	57	.335"	3.0"	.602"	4.5°	Mid
TOUR AD VR 5 X	ADVR5-X	X-Stiff	46"	60	.335"	3.0"	.606"	4.5°	Mid
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD VR 6 SR	ADVR6-SR	Stiff Regular	46"	63	.335"	3.0"	.598"	3.2°	Mid
TOUR AD VR 6 S	ADVR6-S	Stiff	46"	65	.335"	3.0"	.600"	3.2°	Mid
TOUR AD VR 6 X	ADVR6-X	X-Stiff	46"	66	.335"	3.0"	.602"	3.2°	Mid
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD VR 7 S	ADVR7-S	Stiff	46"	73	.335"	3.0"	.604"	3.0°	Mid
TOUR AD VR 7 X	ADVR7-X	X-Stiff	46"	75	.335"	3.0"	.606"	3.0°	Mid
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD VR 8 S	ADVR8-S	Stiff	46"	85	.335"	3.0"	.604"	2.6°	Mid
TOUR AD VR 8 X	ADVR8-X	X-Stiff	46"	86	.335"	3.0"	.606"	2.6°	Mid

Tip Trimming for Standard Bore Heads: Driver: 0.0", #3 wood: .5", #5 Wood or greater 1.0", then Butt Cut to desired club length after assembly.



with TORAYCA T1100G

PROSCHOICEGOLFSHAFTS.COM