



New for 2020, Graphite Design introduces the latest in the Tour AD premium line of golf shafts, the *Graphite Design Tour AD XC* – designed for "Xtra Carry". Designed and manufactured at the Graphite Design Japan factory headquarters, the new **Tour AD XC** wood shafts are black with silver and red accents, a silver fade at the tip and finished with a matte clear coat.

The **Tour AD XC**, like the other high performance Tour AD wood shafts, utilizes premium, aerospace quality carbon-fiber materials and are available in 40g R2, R1 and S flex, 50g R2, R1, S and X flex, 60g SR, S, X and TX flex, 70g S, X and TX flex and 80g S and X flex.

The **Tour AD XC** shaft profile is softer in the butt section, stiff in the center section and has a stiff tip to promote low/mid launch angle and low spin with the ball. The **Tour AD XC** also utilizes the brand new TORAYCA® M40X carbon-fiber pre-preg in the Mid to Tip Section of the shaft as well as the TORAYCA® T1100G carbon-fiber pre-preg with NANOALLOY® technology in the tip section of the shaft for unrivaled shaft stability and precise ball control without the loss of the exceptional feel that Graphite Design shafts are so well known for.

Get fit by your local professional club fitter into the new **Graphite Design Tour AD XC** and get ready to experience the **X**tra **C**arry you are looking for to lower your scores.

MSRP \$500 PROSCHOICEGOLFSHAFTS.COM 760-476-9598



SHAFT SPECIFICATIONS								
Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
ADXC4-R2	Lite/Senior	46"	47g	.335"	3.0"	.593"	5.7°	Mid/High
ADXC4-R1	Regular	46"	47g	.335"	3.0"	.593"	5.7°	Mid/High
ADXC4-S	Stiff	46"	48g	.335"	3.0"	.593"	5.7°	Mid/High
Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
ADXC5-R2	Lite/Senior	46"	54g	.335"	3.0"	.594"	4.3°	Mid/High
ADXC5-R1	Regular	46"	54g	.335"	3.0"	.594"	4.2°	Mid/High
ADXC5-S	Stiff	46"	56g	.335"	3.0"	.596"	4.2°	Mid/High
ADXC5-X	X-Stiff	46"	58g	.335"	3.0"	.600"	4.2°	Mid/High
Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
ADXC6-SR	Stiff Regular	46"	62g	.335"	3.0"	.596"	3.2°	Mid/High
ADXC6-S	Stiff	46"	64g	.335"	3.0"	.598"	3.2°	Mid/High
ADXC6-X	X-Stiff	46"	65g	.335"	3.0"	.600"	3.2°	Mid/High
ADXC6-TX	Tour X-Stiff	46"	67.5g	.335"	3.0"	.602"	3.2°	Mid/High
Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
ADXC7-S	Stiff	46"	73g	.335"	3.0"	.598"	3.0°	Mid/High
ADXC7-X	X-Stiff	46"	75g	.335"	3.0"	.600"	3.0°	Mid/High
ADXC7-TX	Tour X-Stiff	46"	76.5g	.335"	3.0"	.602"	3.0°	Mid/High
Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
ADXC8-S	Stiff	46"	83g	.335"	3.0"	.604"	2.8°	Mid/High
ADVCO V	A Crift	46"	85g	.335"	3.0"	.606"	2.8°	Mid/High
	ADXC4-R2 ADXC4-R1 ADXC4-S Part Number ADXC5-R2 ADXC5-R1 ADXC5-S ADXC5-X Part Number ADXC6-SR ADXC6-SR ADXC6-TX Part Number ADXC7-TX Part Number ADXC7-TX Part Number	ADXC4-R2 Lite/Senior ADXC4-R1 Regular ADXC4-S Stiff Part Number Flex ADXC5-R2 Lite/Senior ADXC5-R1 Regular ADXC5-R3 Stiff ADXC5-S Stiff ADXC5-X X-Stiff Part Number Flex ADXC6-SR Stiff Regular ADXC6-SR Stiff Regular ADXC6-SR Stiff Regular ADXC6-SR Stiff Regular ADXC6-S Stiff ADXC6-TX Tour X-Stiff Part Number Flex ADXC7-X X-Stiff ADXC7-X X-Stiff ADXC7-X Tour X-Stiff ADXC7-X Tour X-Stiff ADXC7-X Tour X-Stiff	Part Number Flex Length ADXC4-R2 Lite/Senior 46" ADXC4-R1 Regular 46" ADXC4-S Sriff 46" Part Number Flex Length ADXC5-R2 Lite/Senior 46" ADXC5-R1 Regular 46" ADXC5-S Sriff 46" Part Number Flex Length ADXC5-X X-Stiff 46" ADXC6-SR Sriff Regular 46" ADXC6-S Sriff 46" ADXC6-X X-Stiff 46" ADXC6-X X-Stiff 46" ADXC6-TX Tour X-Stiff 46" ADXC7-S Sriff 46" ADXC7-X X-Stiff 46" ADXC7-TX Tour X-Stiff 46" ADXC8-S Sriff 46"	Part Number Flex Length Wt ADXC4-R2 Lite/Senior 46" 47g ADXC4-R1 Regular 46" 47g ADXC4-S Stiff 46" 48g Part Number Flex Length Wt ADXC5-R2 Lite/Senior 46" 54g ADXC5-R1 Regular 46" 54g ADXC5-S Stiff 46" 58g Part Number Flex Length Wt ADXC6-SR Stiff Regular 46" 62g ADXC6-S Stiff 46" 64g ADXC6-S Stiff 46" 65g ADXC6-X X-Stiff 46" 67.5g Part Number Flex Length Wt ADXC7-S Stiff 46" 73g ADXC7-S X-Stiff 46" 75g ADXC7-X X-Stiff 46" 76.5g Part Number Flex Length Wt <	Part Number Flex Length Wt Tip OD ADXC4-R2 Lite/Senior 46" 47g .335" ADXC4-R1 Regular 46" 47g .335" ADXC4-S Stiff 46" 48g .335" Part Number Flex Length Wt Tip OD ADXC5-R2 Lite/Senior 46" 54g .335" ADXC5-R1 Regular 46" 54g .335" ADXC5-S Stiff 46" 58g .335" Part Number Flex Length Wt Tip OD ADXC5-X X-Stiff 46" 58g .335" Part Number Flex Length Wt Tip OD ADXC6-SR Stiff Regular 46" 62g .335" ADXC6-S Stiff 46" 64g .335" ADXC6-X X-Stiff 46" 67.5g .335" Part Number Flex Length Wt Tip OD	Part Number Flex Length Wt Tip OD Tip Para. ADXC4-R2 Lite/Senior 46" 47g .335" 3.0" ADXC4-R1 Regular 46" 47g .335" 3.0" ADXC4-S Stiff 46" 48g .335" 3.0" Part Number Flex Length Wt Tip OD Tip Para. ADXC5-R2 Lite/Senior 46" 54g .335" 3.0" ADXC5-R1 Regular 46" 54g .335" 3.0" ADXC5-S Stiff 46" 56g .335" 3.0" ADXC5-X X-Stiff 46" 58g .335" 3.0" Part Number Flex Length Wt Tip OD Tip Para. ADXC6-SR Stiff Regular 46" 62g .335" 3.0" ADXC6-S Stiff 46" 64g .335" 3.0" ADXC6-TX Tour X-Stiff 46" 67.5g .335"	Part Number Flex Length Wt Tip OD Tip Para. Butt OD ADXC4-R2 Lite/Senior 46" 47g .335" 3.0" .593" ADXC4-R1 Regular 46" 47g .335" 3.0" .593" ADXC4-S Stiff 46" 48g .335" 3.0" .593" Part Number Flex Length Wt Tip OD Tip Para. Butt OD ADXC5-R2 Lite/Senior 46" 54g .335" 3.0" .594" ADXC5-R1 Regular 46" 54g .335" 3.0" .594" ADXC5-S Stiff 46" 56g .335" 3.0" .596" ADXC5-X X-Stiff 46" 58g .335" 3.0" .600" Part Number Flex Length Wt Tip OD Tip Para. Butt OD ADXC6-S Stiff 46" 62g .335" 3.0" .598" ADXC6-TX	Part Number Flex Length Wt Tip OD Tip Para. Butt OD Torque ADXC4-R2 Lite/Senior 46" 47g .335" 3.0" .593" 5.7° ADXC4-R1 Regular 46" 47g .335" 3.0" .593" 5.7° ADXC4-S Stiff 46" 48g .335" 3.0" .593" 5.7° Part Number Flex Length Wt Tip OD Tip Para. Butt OD Torque ADXC5-R2 Lite/Senior 46" 54g .335" 3.0" .594" 4.3° ADXC5-R1 Regular 46" 54g .335" 3.0" .594" 4.2° ADXC5-S Stiff 46" 56g .335" 3.0" .596" 4.2° Part Number Flex Length Wt Tip OD Tip Para. Butt OD Torque ADXC6-SR Stifff 46" 62g .335" 3.0" .596" 3.2°

Tip Trimming for Standard Bore Heads: Driver: 0.0", #3 wood: .5", #5 Wood or greater 1.0", then Butt Cut to desired club length after assembly.



PROSCHOICEGOLFSHAFTS.COM