



Pro's Choice

EXCLUSIVE DISTRIBUTOR FOR **GRAPHITE DESIGN**



TOUR AD WOOD SHAFT FITTING GUIDE AND SHAFT COMPARISON CHART

| RECOMMENDED SHAFT MODEL BASED ON DESIRED LAUNCH ANGLE AND SPIN RATE CHARACTERISTICS: | | | | | | |
|--|----------|--|--|--|-----------------|--|
| LAUNCH | HIGH | TOUR AD IZ-6 | TOUR AD IZ-4 TOUR AD IZ-5 | CHICHIBU R & SR TOUR AD VR-4 TOUR AD F-55 FWY CHICHIBU S & S+ | TOUR AD SL II-4 | |
| | | TOUR AD DI-6 TOUR AD VR-6 TOUR AD IZ-7 | TOUR AD TP-4 TOUR AD GP-4 TOUR AD VR-5 TOUR AD DI-5 | TOUR AD F-65 FWY TOUR AD DJ-5 TOUR AD F-75 FWY TOUR AD F-85 FWY | | |
| | MID/HIGH | TOUR AD TP-6 TOUR AD DI-7 | TOUR AD MJ-5 TOUR AD TP-5 | TOUR AD DJ-6 | TOUR AD SL II-5 | |
| | | TOUR AD VR-7 TOUR AD IZ-8 TOUR AD TP-7 | TOUR AD MT-5 TOUR AD MJ-6 TOUR AD GP-5 | | | |
| | MID | TOUR AD VR-8 TOUR AD DI-8 TOUR AD TP-8 TOUR AD GP-6 | TOUR AD XC-4 TOUR AD XC-5 TOUR AD BB-5 TOUR AD MT-6 TOUR AD MJ-7 | TOUR AD DJ 7 | | |
| | | TOUR AD GP-7 TOUR AD GP-8 TOUR AD DI-9 | TOUR AD MJ-8 | TOUR AD DJ-8 | | |
| | LOW/MID | TOUR AD BB-6 TOUR AD BB-7 TOUR AD XC-6 TOUR AD XC-7 | TOUR AD MT-7 | | | |
| | | TOUR AD BB-8 TOUR AD XC-8 | TOUR AD MT-8 | | | |
| | LOW | TOUR AD M9003-6 | | | | |
| | | TOUR AD M9003-7 | | | | |
| | LOW | LOW/MID | MID | MID/HIGH | HIGH | |
| SPIN | | | | | | |

| RECOMMENDED SHAFT FLEX GUIDE FOR TOUR AD WOODS BASED ON DRIVER SWING SPEED: | | | | | | | |
|---|-----------------------------------|----------------------------------|-------------------------|-------------------------------|----------------|------------------|------------------------|
| DRIVER SWING SPEED | Less Than 70 MPH | 71-85 MPH | 86-95 MPH | 92-98 MPH | 96-105 MPH | 105+ MPH | 110+ MPH |
| SHAFT FLEX | RR2 & RR1 Flex (Ladies/Soft Lite) | R2 Flex (Lite/Senior) | R1 Flex (Regular) | SR Flex* (Stiff Regular) | S Flex (Stiff) | X Flex (X-Stiff) | TX Flex (Tour X-Stiff) |
| RECOMMENDED SHAFT FLEX GUIDE FOR CHICHIBU SHAFTS BASED ON DRIVER SWING SPEED: | | | | | | | |
| DRIVER SWING SPEED | Less than 70 MPH | 71-75 MPH | 76-81 MPH | 81-85 MPH | | | |
| SHAFT FLEX | Chichibu R Flex (Regular) | Chichibu SR Flex (Stiff Regular) | Chichibu S Flex (Stiff) | Chichibu S+ Flex (Stiff Plus) | | | |

* Stiff Regular (SR) Flex shafts are available in the "Tour AD" wood models only.
Pro's Choice Golf Shafts encourages consulting a PGA Professional or qualified Graphite Design Club Fitter to help you determine the correct shaft weight, flex and length for your swing profile and to meet your goals.

| GRAPHITE DESIGN WOOD SHAFT COMPARISON CHART: | | | |
|--|--------------|-------------|-------------|
| SHAFT MODEL | BUTT SECTION | MID SECTION | TIP SECTION |
| TOUR AD XC | SOFT | STIFF | STIFF |
| TOUR AD VR | FIRM+ | MEDIUM+ | FIRM |
| MAD PRO | FIRM | STIFF | FIRM |
| MAD Std. | MEDIUM+ | FIRM+ | MEDIUM+ |
| TOUR AD IZ | FIRM | MEDIUM | FIRM+ |
| TOUR AD TP | FIRM | FIRM | STIFF |
| TOUR AD F-Series FWY | FIRM | MEDIUM | SOFT |
| TOUR AD GP | FIRM+ | FIRM | VERY STIFF |
| TOUR AD M9003 | MEDIUM | FIRM | STIFF+ |
| TOUR AD MJ | MEDIUM+ | FIRM+ | MEDIUM |
| TOUR AD MT | MEDIUM | STIFF+ | FIRM |
| TOUR AD BB | SOFT | STIFF | FIRM |
| TOUR AD DJ | STIFF | MEDIUM | SOFT |
| TOUR AD DI | MEDIUM | MEDIUM | STIFF |
| TOUR AD SL II | MEDIUM | MEDIUM | SOFT |
| YS NanoReloaded | MEDIUM | MEDIUM | MEDIUM |

LEGEND DESCRIBING THE SHAFT STIFFNESS FROM STIFFEST TO SOFTEST:
VERY STIFF → STIFF → FIRM → MEDIUM → SOFT

Pro's Choice Contact Information:
Sales: Bill McPherson
b.mcpherson@proschoicegolfshafts.com
Phone: 619-454-6283

UPDATED: July 1, 2020



Pro's Choice
EXCLUSIVE DISTRIBUTOR FOR **GRAPHITE DESIGN**.



TOUR AD HYBRID & IRON FITTING GUIDE

| RECOMMENDED SHAFT MODEL BASED ON DESIRED LAUNCH ANGLE AND SPIN RATE CHARACTERISTICS: | | | | | | |
|--|----------|---------|---------------|---|-----|----------|
| LAUNCH | HIGH | | | TOUR AD 50 IRON | | |
| | MID/HIGH | | TOUR AD IZ 65 | TOUR AD HY 65 & 75 TOUR AD 65 IRON | | |
| | | | TOUR AD IZ 75 | TOUR AD HY 85 TOUR AD HY 95 TOUR AD 75 IRON | | |
| | MID | | | TOUR AD DRIVING IRON 85 TOUR AD 85 IRON TOUR AD DI 75 TOUR AD DI 85 | | |
| | | | | TOUR AD IZ 85 TOUR AD DRIVING IRON 95 TOUR AD 95 IRON TOUR AD DI 95 TOUR AD IZ 95 TOUR AD DI 105 | | |
| | | LOW/MID | | TOUR AD 105 IRON | | |
| | | | | TOUR AD 115 IRON | | |
| | LOW | | | | | |
| | | | | | | |
| | | | LOW | LOW/MID | MID | MID/HIGH |
| SPIN | | | | | | |

| RECOMMENDED SHAFT FLEX GUIDE BASED ON DRIVER SWING SPEED: | | | |
|---|---------------------|-------------------|---------------------|
| DRIVER SWING SPEED | 86-95 MPH | 96-105 MPH | 105+ MPH |
| SHAFT FLEX | R Flex (Regular) | S Flex (Stiff) | X Flex (X-Stiff) |
| Pro's Choice Golf Shafts encourages consulting a PGA Professional or qualified Graphite Design Club Fitter to help you determine the correct shaft weight, flex and length for your swing profile and to meet your goals. | | | |

| HYBRID SHAFT BEND PROFILE CHART: | | | |
|--|--------------|-------------|-------------|
| SHAFT MODEL | BUTT SECTION | MID SECTION | TIP SECTION |
| TOUR AD IZ 65/75 | MEDIUM | FIRM | FIRM |
| TOUR AD IZ 85/95 | FIRM | FIRM | STIFF |
| TOUR AD DI | SOFT | MEDIUM+ | STIFF |
| TOUR AD HY | MEDIUM | MEDIUM | MEDIUM |
| LEGEND DESCRIBING THE SHAFT STIFFNESS FROM STIFFEST TO SOFTEST: VERY STIFF → STIFF → FIRM → MEDIUM → SOFT | | | |

Pro's Choice Contact Information:

Sales: Bill McPherson
b.mcpherson@proschoicegolfshafts.com
Phone: 619-454-6283

PROSCHOICEGOLFSHAFTS.COM



Pro's Choice
EXCLUSIVE DISTRIBUTOR FOR **GRAPHITE DESIGN.**



US SPEC SHAFT FITTING GUIDE

| RECOMMENDED SHAFT MODEL BASED ON DESIRED LAUNCH ANGLE AND SPIN RATE CHARACTERISTICS: | | | | | | |
|--|----------|------------|-----------------------------|---|----------|------|
| LAUNCH | HIGH | | | G-TECH L FLEX MAD 45 | | |
| | MID/HIGH | | | MAD 55 G-TECH A FLEX YS FIVE RELOADED | | |
| | | | | G-TECH R FLEX | | |
| | MID | MAD PRO 65 | MAD 65 | G-TECH S FLEX YS SIX RELOADED | | |
| | | MAD PRO 75 | YS SEVEN RELOADED MAD 75 | | | |
| | LOW/MID | | | | | |
| | | | | | | |
| | LOW | | | | | |
| | | | | | | |
| | | LOW | LOW/MID | MID | MID/HIGH | HIGH |
| SPIN | | | | | | |

| RECOMMENDED SHAFT FLEX GUIDE BASED ON DRIVER SWING SPEED: | | | | | |
|---|------------------|----------------------------|------------------|----------------|------------------|
| DRIVER SWING SPEED | Less Than 70 MPH | 71-85 MPH | 86-95 MPH | 96-105 MPH | 105+ MPH |
| SHAFT FLEX | L Flex (Ladies) | A or RR Flex (Lite/Senior) | R Flex (Regular) | S Flex (Stiff) | X Flex (X-Stiff) |
| Pro's Choice Golf Shafts encourages consulting a PGA Professional or qualified Graphite Design Club Fitter to help you determine the correct shaft weight, flex and length for your swing profile and to meet your goals. | | | | | |

| US SPEC WOOD SHAFT BEND PROFILE CHART: | | | |
|--|--------------|-------------|-------------|
| SHAFT MODEL | BUTT SECTION | MID SECTION | TIP SECTION |
| MAD STD | MEDIUM+ | FIRM+ | MEDIUM+ |
| MAD PRO | FIRM | STIFF | FIRM |
| YS NanoReloaded | MEDIUM | MEDIUM | MEDIUM |
| LEGEND DESCRIBING THE SHAFT STIFFNESS FROM STIFFEST TO SOFTEST: VERY STIFF → STIFF → FIRM → MEDIUM → SOFT | | | |

Pro's Choice Contact Information:

Sales: Bill McPherson
b.mcpherson@proschoicegolfs shafts.com
Phone: 619-454-6283

PROSCHOICEGOLFSHAFTS.COM