



The Graphite Design **Tour AD XC** – designed for “**X**tra **C**arry”, was Designed and is manufactured at the Graphite Design Japan factory headquarters and is black with silver and red accents, a silver fade at the tip and finished with a matte clear coat.

The **Tour AD XC**, like the other high performance Tour AD wood shafts, utilizes premium, aerospace quality carbon-fiber materials and are available in 40g R2, R1 and S flex, 50g R2, R1, S and X flex, 60g SR, S, X and TX flex, 70g S, X and TX flex and 80g S and X flex.

The **Tour AD XC** shaft profile is softer in the butt section, stiff in the center section and has a stiff tip to promote low/mid launch angle and low spin with the ball. The **Tour AD XC** also utilizes the brand new TORAYCA® M40X carbon-fiber pre-preg in the Mid to Tip Section of the shaft as well as the TORAYCA® T1100G carbon-fiber pre-preg with NANOALLOY® technology in the tip section of the shaft for unrivaled shaft stability and precise ball control without the loss of the exceptional feel that Graphite Design shafts are so well known for.

Get fit by your local professional club fitter into the new Graphite Design **Tour AD XC** and get ready to experience the **X**tra **C**arry you are looking for to lower your scores.

MSRP \$500
 PROSCHOICEGOLFSHAFTS.COM
 760-476-9598



SHAFT SPECIFICATIONS

Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD XC4 R2	ADXC4-R2	Lite/Senior	46"	47g	.335"	3.0"	.593"	5.7°	Mid/High
TOUR AD XC 4 R1	ADXC4-R1	Regular	46"	47g	.335"	3.0"	.593"	5.7°	Mid/High
TOUR AD XC 4 S	ADXC4-S	Stiff	46"	48g	.335"	3.0"	.593"	5.7°	Mid/High
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD XC 5 R2	ADXC5-R2	Lite/Senior	46"	54g	.335"	3.0"	.594"	4.3°	Mid/High
TOUR AD XC 5 R1	ADXC5-R1	Regular	46"	54g	.335"	3.0"	.594"	4.2°	Mid/High
TOUR AD XC 5 S	ADXC5-S	Stiff	46"	56g	.335"	3.0"	.594"	4.2°	Mid/High
TOUR AD XC 5 X	ADXC5-X	X-Stiff	46"	58g	.335"	3.0"	.600"	4.2°	Mid/High
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD XC 6 SR	ADXC6-SR	Stiff Regular	46"	62g	.335"	3.0"	.596"	3.2°	Mid/High
TOUR AD XC 6 S	ADXC6-S	Stiff	46"	64g	.335"	3.0"	.598"	3.2°	Mid/High
TOUR AD XC 6 X	ADXC6-X	X-Stiff	46"	65g	.335"	3.0"	.600"	3.2°	Mid/High
TOUR AD XC 6 TX	ADXC6-TX	Tour X-Stiff	46"	67.5g	.335"	3.0"	.602"	3.2°	Mid/High
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD XC 7 S	ADXC7-S	Stiff	46"	73g	.335"	3.0"	.598"	3.0°	Mid/High
TOUR AD XC 7 X	ADXC7-X	X-Stiff	46"	75g	.335"	3.0"	.600"	3.0°	Mid/High
TOUR AD XC 7 TX	ADXC7-TX	Tour X-Stiff	46"	76.5g	.335"	3.0"	.602"	3.0°	Mid/High
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD XC 8 S	ADXC8-S	Stiff	46"	83g	.335"	3.0"	.604"	2.8°	Mid/High
TOUR AD XC 8 X	ADXC8-X	X-Stiff	46"	85g	.335"	3.0"	.606"	2.8°	Mid/High

Tip Trimming for Standard Bore Heads: Driver: 0.0", #3 wood: .5", #5 Wood or greater 1.0", then Butt Cut to desired club length after assembly.



PROSCHOICEGOLFSHAFTS.COM