



# TOUR AD WOOD SHAFT FITTING GUIDE AND SHAFT COMPARISON CHART

	RECOMMENDED SHAFT MODEL BASED ON DESIRED LAUNCH ANGLE AND SPIN RATE CHARACTERISTICS:							
	НІБН	TOUR AD 1Z-6	TOUR AD IZ-4 Tour ad IZ-5 Tour ad UB-4	CHICHIBU R & SR TOUR AD VR-4 TOUR AD F-55 FWY CHICHIBU S & S+	TOUR AD SL 11-4			
		TOUR AD DI-6 TOUR AD VR-6 TOUR AD IZ-7	TOUR AD TP-4 TOUR AD GP-4 TOUR AD VR-5 TOUR AD DI-5	TOUR AD F-65 FWY TOUR AD F-75 FWY TOUR AD F-85 FWY				
		TOUR AD TP-6 TOUR AD DI-7	TOUR AD TP-5	TOUR AD MJ-5	TOUR AD SL II-5			
	MID/HIGH	TOUR AD VR-7 Tour ad IZ-8 Tour ad TP-7	TOUR AD MJ-6 Tour Ad GP-5					
LAUNCH	MID	TOUR AD HD-6 TOUR AD HD-7 TOUR AD VR-8 TOUR AD DI-8 TOUR AD TP-8 TOUR AD GP-6	TOUR AD UB-5 TOUR AD HD-4 TOUR AD XC-4 TOUR AD UB-6 TOUR AD HD-5 TOUR AD XC-5 TOUR AD BB-5					
		TOUR AD HD-8 TOUR AD GP-7 TOUR AD GP-8 TOUR AD DI-9	TOUR AD MJ-7 TOUR AD MJ-8 TOUR AD UB-7 TOUR AD UB-8					
	LOW/MID	TOUR AD BB-6 TOUR AD BB-7 TOUR AD XC-6 TOUR AD XC-7						
		TOUR AD BB-8 TOUR AD XC-8						
	LOW	TOUR AD M9003-6						
	-5	TOUR AD M9003-7						
		LOW	LOW/MID	MID	MID/HIGH	HIGH		
		SPIN						

RECOMMENDED SHAFT FLEX GUIDE FOR TOUR AD WOODS BASED ON DRIVER SWING SPEED:							
DRIVER SWING SPEED	Less Than 70 MPH	71-85 MPH	86-95 MPH	92-98 MPH	96-105 MPH	105+ MPH	110+ MPH
SHAFT FLEX	RR2 & RR1 Flex (Ladies/Soft Lite)	R2 Flex (Lite/Senior)	R1 Flex (Regular)	SR Flex* (Stiff Regular)	S Flex (Stiff)	X Flex (X-Stiff)	TX Flex (Tour X-Stiff)
RECOMMENDED SHAFT FLEX GUIDE FOR CHICHIBU SHAFTS BASED ON DRIVER SWING SPEED:							
DRIVER SWING SPEED Less than 70 MPH 71-75 MPH 76-81 MPH 81-85 MPH							
SHAFT FLEX Chichibu R Flex Chichibu SR Flex Chichibu S Flex Chichibu S Flex (Regular) (Stiff Regular) (Stiff) (Stiff Plus)							
* Stiff Regular ( SR ) Flex shafts are available in the " Tour AD" wood models only.							

Pro's Choice Golf Shafts encourages consulting a PGA Professional or qualified Graphite Design Club Fitter to help you determine the correct shaft weight, flex and length for your swing profile and to meet your goals.

GRAPHITE DESIGN WOOD SHAFT COMPARISON CHART:							
SHAFT MODEL	BUTT SECTION	MID SECTION	TIP SECTION				
TOUR AD UB	MEDIUM+	MEDIUM+	STIFF+				
TOUR AD HD	FIRM	FIRM	FIRM+				
TOUR AD XC	SOFT	STIFF	STIFF				
TOUR AD VR	FIRM+	MEDIUM+	FIRM				
MAD PRO	FIRM	STIFF	FIRM				
MAD Std.	MEDIUM+	FIRM+	MEDIUM+				
TOUR AD IZ	FIRM	MEDIUM	FIRM+				
TOUR AD TP	FIRM	FIRM	STIFF				
TOUR AD F-Series FWY	FIRM	MEDIUM	SOFT				
TOUR AD GP	FIRM+	FIRM	VERY STIFF				
TOUR AD M9003	MEDIUM	FIRM	STIFF+				
TOUR AD MJ	MEDIUM+	FIRM+	MEDIUM				
TOUR AD BB	SOFT	STIFF	FIRM				
TOUR AD DI	MEDIUM	MEDIUM	STIFF				
TOUR AD SL II	MEDIUM	MEDIUM	SOFT				
	LEGEND DESCRIBING THE SHAFT STIFFNESS FROM STIFFEST TO SOFTEST:						

 $\mathsf{VERY}\,\mathsf{STIFF}\,\to\,\mathsf{STIFF}\,\to\,\mathsf{FIRM}\,\to\,\mathsf{MEDIUM}\,\to\,\mathsf{SOFT}$ 

Pro's Choice Contact Information:

Sales: Bill McPherson b.mcpherson@proschoicegolfshafts.com

Phone: 619-454-6283 UPDATED: August 31, 2021





# **TOUR AD HYBRID & IRON FITTING GUIDE**

	RECOMMENDED SHAFT MODEL BASED ON DESIRED LAUNCH ANGLE AND SPIN RATE CHARACTERISTICS:							
	HIGH			TOUR AD 50 IRON				
	MID/HIGH			TOUR AD 55 IRON TOUR AD HY 65 & 75 TOUR AD 65 IRON TOUR AD IZ 65				
				TOUR AD HY 85 TOUR AD HY 95 TOUR AD 75 IRON TOUR AD IZ 75				
LAUNCH	MID		TOUR AD DI 85 HYBRID	TOUR AD DRIVING IRON 85 TOUR AD 85 IRON TOUR AD DI 75				
			TOUR AD DI 95 HYBRID TOUR AD DI 105 HYBRID	TOUR AD DRIVING IRON 95 TOUR AD 95 IRON				
	LOW/MID		TOUR AD IZ 85 HYBRID TOUR AD IZ 95 HYBRID					
			TOUR AD 105 IRON TOUR AD 115 IRON					
	LOW							
		LOW	LOW/MID	MID	MID/HIGH	HIGH		
SPIN								

RECOMMENDED SHAFT FLEX GUIDE BASED ON DRIVER SWING SPEED:							
DRIVER SWING SPEED	86-95 MPH	96-105 MPH	105+ MPH				
SHAFT FLEX	R Flex (Regular)	S Flex (Stiff)	X Flex (X-Stiff)				

Pro's Choice Golf Shafts encourages consulting a PGA Professional or qualified Graphite Design Club Fitter to help you determine the correct shaft weight, flex and length for your swing profile and to meet your goals.

HYBRID SHAFT BEND PROFILE CHART:							
SHAFT MODEL	BUTT SECTION	MID SECTION	TIP SECTION				
TOUR AD IZ 65/75 HYBRID	MEDIUM	FIRM	FIRM				
TOUR AD IZ 85/95 HYBRID	FIRM	FIRM	STIFF				
TOUR AD DI HYBRID	SOFT	MEDIUM+	STIFF				
TOUR AD HY HYBRID	MEDIUM	MEDIUM	MEDIUM				
<del></del>	LEGEND DESCRIBING THE SHAFT STIFFNESS FROM STIFFEST TO SOFTEST: VERY STIFF $ ightarrow$ STIFF $ ightarrow$ Firm $ ightarrow$ Medium $ ightarrow$ Soft						

### Pro's Choice Contact Information:

Sales: Bill McPherson b.mcpherson@proschoicegolfshafts.com

Phone: 619-454-6283

PROSCHOICEGOLFSHAFTS.COM





# **US SPEC SHAFT FITTING GUIDE**

		RECOMMENDED SHAFT A	MODEL BASED ON DESIRED	LAUNCH ANGLE AND SPI	N RATE CHARACTERISTICS:		
	HIGH			G-TECH L FLEX MAD 45			
	MID /IIICII			MAD 55 G-TECH A FLEX			
	MID/HIGH			G-TECH R FLEX			
LOT HOS	MID	MAD PRO 65	MAD 65	G-TECH S FLEX			
LAUNCH		MAD PRO 75	MAD 75				
	LOW/MID						
	LOW						
	25						
		LOW	LOW/MID	MID	MID/HIGH	HIGH	
		SPIN					

RECOMMENDED SHAFT FLEX GUIDE BASED ON DRIVER SWING SPEED:							
DRIVER SWING SPEED	Less Than 70 MPH	71-85 MPH	86-95 MPH	96-105 MPH	105+ MPH		
SHAFT FLEX	L Flex (Ladies )	A or RR Flex (Lite/Senior)	R Flex (Regular)	S Flex (Stiff)	X Flex (X-Stiff)		

Pro's Choice Golf Shafts encourages consulting a PGA Professional or qualified Graphite Design Club Fitter to help you determine the correct shaft weight, flex and length for your swing profile and to meet your goals.

US SPEC WOOD SHAFT BEND PROFILE CHART:							
SHAFT MODEL BUTT SECTION MID SECTION TIP SECTION							
mad Std	MEDIUM+	FIRM+	MEDIUM+				
MAD PRO	FIRM	STIFF	FIRM				
LEGEND DESCRIBING THE SHAFT STIFFNESS FROM STIFFEST TO SOFTEST: VERY STIFF $ ightarrow$ STIFF $ ightarrow$ FIRM $ ightarrow$ Medium $ ightarrow$ Soft							

### Pro's Choice Contact Information:

Sales: Bill McPherson b.mcpherson@proschoicegolfshafts.com

Phone: 619-454-6283

PROSCHOICEGOLFSHAFTS.COM