



Pro's Choice

EXCLUSIVE DISTRIBUTOR FOR **GRAPHITE DESIGN**




TOUR AD WOOD SHAFT FITTING GUIDE AND SHAFT COMPARISON CHART

RECOMMENDED SHAFT MODEL BASED ON DESIRED LAUNCH ANGLE AND SPIN RATE CHARACTERISTICS:						
LAUNCH	HIGH	TOUR AD IZ-6	TOUR AD IZ-4 TOUR AD IZ-5 TOUR AD UB-4	CHICHIBU R & SR TOUR AD VR-4 TOUR AD F-55 FWY CHICHIBU S & S+	TOUR AD SL II-4	
		TOUR AD DI-6 TOUR AD VR-6 TOUR AD IZ-7	TOUR AD TP-4 TOUR AD GP-4 TOUR AD VR-5 TOUR AD DI-5	TOUR AD F-65 FWY TOUR AD F-75 FWY TOUR AD F-85 FWY		
	MID/HIGH	TOUR AD TP-6 TOUR AD DI-7	TOUR AD TP-5	TOUR AD MJ-5 TOUR AD CQ-4 TOUR AD CQ-5	TOUR AD SL II-5	
		TOUR AD VR-7 TOUR AD IZ-8 TOUR AD TP-7	TOUR AD MJ-6 TOUR AD GP-5	TOUR AD CQ-6 TOUR AD CQ-7 TOUR AD CQ-8		
	MID	TOUR AD HD-6 TOUR AD HD-7 TOUR AD VR-8 TOUR AD DI-8 TOUR AD TP-8 TOUR AD GP-6	TOUR AD UB-5 TOUR AD HD-4 TOUR AD XC-4 TOUR AD UB-6 TOUR AD HD-5 TOUR AD XC-5 TOUR AD BB-5			
		TOUR AD HD-8 TOUR AD GP-7 TOUR AD GP-8 TOUR AD DI-9	TOUR AD MJ-7 TOUR AD MJ-8 TOUR AD UB-7 TOUR AD UB-8			
		TOUR AD BB-6 TOUR AD BB-7 TOUR AD XC-6 TOUR AD XC-7				
		TOUR AD BB-8 TOUR AD XC-8				
	LOW/MID	TOUR AD M9003-6				
		TOUR AD M9003-7				
LOW						
		LOW	LOW/MID	MID	MID/HIGH	HIGH
SPIN						

RECOMMENDED SHAFT FLEX GUIDE FOR TOUR AD WOODS BASED ON DRIVER SWING SPEED:							
DRIVER SWING SPEED	Less Than 70 MPH	71-85 MPH	86-95 MPH	92-98 MPH	96-105 MPH	105+ MPH	110+ MPH
SHAFT FLEX	RR2 & RR1 Flex (Ladies/Soft Lite)	R2 Flex (Lite/Senior)	R1 Flex (Regular)	SR Flex* (Stiff Regular)	S Flex (Stiff)	X Flex (X-Stiff)	TX Flex (Tour X-Stiff)
RECOMMENDED SHAFT FLEX GUIDE FOR CHICHIBU SHAFTS BASED ON DRIVER SWING SPEED:							
DRIVER SWING SPEED	Less than 70 MPH	71-75 MPH	76-81 MPH	81-85 MPH			
SHAFT FLEX	Chichibu R Flex (Regular)	Chichibu SR Flex (Stiff Regular)	Chichibu S Flex (Stiff)	Chichibu S+ Flex (Stiff Plus)			
* Stiff Regular (SR) Flex shafts are available in the " Tour AD" wood models only.							
Pro's Choice Golf Shafts encourages consulting a PGA Professional or qualified Graphite Design Club Fitter to help you determine the correct shaft weight, flex and length for your swing profile and to meet your goals.							

GRAPHITE DESIGN WOOD SHAFT COMPARISON CHART:			
SHAFT MODEL	BUTT SECTION	MID SECTION	TIP SECTION
TOUR AD CQ	FIRM	FIRM	MEDIUM+
TOUR AD UB	MEDIUM+	MEDIUM+	STIFF+
TOUR AD HD	FIRM	FIRM	FIRM+
TOUR AD XC	SOFT	STIFF	STIFF
TOUR AD VR	FIRM+	MEDIUM+	FIRM
MAD PRO	FIRM	STIFF	FIRM
MAD Std.	MEDIUM+	FIRM+	MEDIUM+
TOUR AD IZ	FIRM	MEDIUM	FIRM+
TOUR AD TP	FIRM	FIRM	STIFF
TOUR AD F-Series FWY	FIRM	MEDIUM	SOFT
TOUR AD GP	FIRM+	FIRM	VERY STIFF
TOUR AD M9003	MEDIUM	FIRM	STIFF+
TOUR AD MJ	MEDIUM+	FIRM+	MEDIUM
TOUR AD BB	SOFT	STIFF	FIRM
TOUR AD DI	MEDIUM	MEDIUM	STIFF
TOUR AD SL II	MEDIUM	MEDIUM	SOFT
LEGEND DESCRIBING THE SHAFT STIFFNESS FROM STIFFEST TO SOFTEST: VERY STIFF → STIFF → FIRM → MEDIUM → SOFT			

Pro's Choice Contact Information:
 Sales: Bill McPherson
 b.mcpherson@proschoicegolfshafts.com
 Phone: 619-454-6283
 UPDATED: July 25, 2022



Pro's Choice

EXCLUSIVE DISTRIBUTOR FOR **GRAPHITE DESIGN**



TOUR AD HYBRID & IRON FITTING GUIDE

RECOMMENDED SHAFT MODEL BASED ON DESIRED LAUNCH ANGLE AND SPIN RATE CHARACTERISTICS:						
LAUNCH	HIGH			TOUR AD 50 IRON		
	MID/HIGH			TOUR AD 55 IRON TOUR AD HY 65 & 75 TOUR AD 65 IRON TOUR AD IZ 65		
				TOUR AD HY 85 TOUR AD HY 95 TOUR AD 75 IRON TOUR AD IZ 75		
	MID		TOUR AD DI 85 HYBRID	TOUR AD DRIVING IRON 85 TOUR AD 85 IRON TOUR AD DI 75		
			TOUR AD DI 95 HYBRID TOUR AD DI 105 HYBRID	TOUR AD DRIVING IRON 95 TOUR AD 95 IRON		
	LOW/MID		TOUR AD IZ 85 HYBRID TOUR AD IZ 95 HYBRID			
			TOUR AD 105 IRON TOUR AD 115 IRON			
	LOW					
		LOW	LOW/MID	MID	MID/HIGH	HIGH
SPIN						

RECOMMENDED SHAFT FLEX GUIDE BASED ON DRIVER SWING SPEED:			
DRIVER SWING SPEED	86-95 MPH	96-105 MPH	105+ MPH
SHAFT FLEX	R Flex (Regular)	S Flex (Stiff)	X Flex (X-Stiff)
Pro's Choice Golf Shafts encourages consulting a PGA Professional or qualified Graphite Design Club Fitter to help you determine the correct shaft weight, flex and length for your swing profile and to meet your goals.			

HYBRID SHAFT BEND PROFILE CHART:			
SHAFT MODEL	BUTT SECTION	MID SECTION	TIP SECTION
TOUR AD IZ 65/75 HYBRID	MEDIUM	FIRM	FIRM
TOUR AD IZ 85/95 HYBRID	FIRM	FIRM	STIFF
TOUR AD DI HYBRID	SOFT	MEDIUM+	STIFF
TOUR AD HY HYBRID	MEDIUM	MEDIUM	MEDIUM
LEGEND DESCRIBING THE SHAFT STIFFNESS FROM STIFFEST TO SOFTEST: VERY STIFF → STIFF → FIRM → MEDIUM → SOFT			

Pro's Choice Contact Information:

Sales: Bill McPherson
 b.mcpherson@proschoicegolfshafts.com
 Phone: 619-454-6283

PROSCHOICEGOLFSHAFTS.COM



Pro's Choice

EXCLUSIVE DISTRIBUTOR FOR **GRAPHITE DESIGN**.



US SPEC SHAFT FITTING GUIDE

RECOMMENDED SHAFT MODEL BASED ON DESIRED LAUNCH ANGLE AND SPIN RATE CHARACTERISTICS:						
LAUNCH	HIGH			G-TECH L FLEX MAD 45		
	MID/HIGH			MAD 55 G-TECH A FLEX		
				G-TECH R FLEX		
	MID	MAD PRO 65	MAD 65	G-TECH S FLEX		
		MAD PRO 75	MAD 75			
	LOW/MID					
	LOW					
		LOW	LOW/MID	MID	MID/HIGH	HIGH
SPIN						

RECOMMENDED SHAFT FLEX GUIDE BASED ON DRIVER SWING SPEED:					
DRIVER SWING SPEED	Less Than 70 MPH	71-85 MPH	86-95 MPH	96-105 MPH	105+ MPH
SHAFT FLEX	L Flex (Ladies)	A or RR Flex (Lite/Senior)	R Flex (Regular)	S Flex (Stiff)	X Flex (X-Stiff)
Pro's Choice Golf Shafts encourages consulting a PGA Professional or qualified Graphite Design Club Fitter to help you determine the correct shaft weight, flex and length for your swing profile and to meet your goals.					

US SPEC WOOD SHAFT BEND PROFILE CHART:			
SHAFT MODEL	BUTT SECTION	MID SECTION	TIP SECTION
MAD STD	MEDIUM+	FIRM+	MEDIUM+
MAD PRO	FIRM	STIFF	FIRM
LEGEND DESCRIBING THE SHAFT STIFFNESS FROM STIFFEST TO SOFTEST: VERY STIFF → STIFF → FIRM → MEDIUM → SOFT			

Pro's Choice Contact Information:

Sales: Bill McPherson
 b.mcpherson@proschoicegolfshafts.com
 Phone: 619-454-6283

PROSCHOICEGOLFSHAFTS.COM

UPDATED: July 25, 2022