



Designed and manufactured at the Graphite Design Japan factory headquarters, the Graphite Design **Tour AD CQ** - **CONQUEST** wood shafts are jet black with gold and red accents and finished with a gloss clear coat.

The **Tour AD CQ**, like the other high performance Tour AD wood shafts, utilizes premium, aerospace quality carbon-fiber materials and are available in 40g R2, R1 and S flex, 50g R2, R1, S and X flex, 60g SR, S, X and TX flex, 70g S, X and TX flex and 80g X flex.

The **Tour AD CQ** shafts features the new **Nitta 2G-Namd** carbon-fiber material technology in the butt section of the shaft and has a bend profile of firm in the handle section, firm in the center section and a medium+ tip section to promote mid-high launch angles and mid ball spin rates. The **Nitta 2G-Namd** material is based on modern carbon nano tube technology that binds the fibers tighter together than standard carbon materials to aid in a higher degree of energy transfer thru the golf club and a more solid impact of the golf ball than shafts without **Nitta 2G-Namd** technology.

Visit your local Graphite Design dealer for a fitting and experience what the new **Tour AD CQ** wood shafts with **Nitta 2G-Namd** can offer in your **CONQUEST** to gain a Tour level of precise **Accuracy** and greater **Distance** that all **Tour AD** shafts are so well known for.

MSRP \$500
 PROSCHOICEGOLFSHAFTS.COM
 760-476-9598



SHAFT SPECIFICATIONS

Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD CQ 4 R2	WCQ4-R2	LITE/SENIOR	46"	47g	.335"	3.0"	.596"	6.1°	LOW/MID
TOUR AD CQ 4 R1	WCQ4-R1	REGULAR	46"	48g	.335"	3.0"	.596"	6.0°	LOW/MID
TOUR AD CQ 4 S	WCQ4-S	STIFF	46"	49g	.335"	3.0"	.600"	6.0°	LOW/MID
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD CQ 5 R2	WCQ5-R2	LITE/SENIOR	46"	53g	.335"	3.0"	.596"	4.6°	LOW/MID
TOUR AD CQ 5 R1	WCQ5-R1	REGULAR	46"	54g	.335"	3.0"	.598"	4.6°	LOW/MID
TOUR AD CQ 5 S	WCQ5-S	STIFF	46"	56g	.335"	3.0"	.600"	4.5°	LOW/MID
TOUR AD CQ 5 X	WCQ5-X	X-STIFF	46"	59g	.335"	3.0"	.604"	4.5°	LOW/MID
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD CQ 6 SR	WCQ6-SR	STIFF REGULAR	46"	62g	.335"	3.0"	.600"	3.4°	LOW/MID
TOUR AD CQ 6 S	WCQ6-S	STIFF	46"	64g	.335"	3.0"	.602"	3.4°	LOW/MID
TOUR AD CQ 6 X	WCQ6-X	X-STIFF	46"	66g	.335"	3.0"	.604"	3.4°	LOW/MID
TOUR AD CQ 6 TX	WCQ6-TX	TOUR X-STIFF	46"	68g	.335"	3.0"	.606"	3.4°	LOW/MID
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD CQ 7 S	WCQ7-S	STIFF	46"	73g	.335"	3.0"	.602"	3.2°	LOW/MID
TOUR AD CQ 7 X	WCQ7-X	X-STIFF	46"	74g	.335"	3.0"	.604"	3.2°	LOW/MID
TOUR AD CQ 7 TX	WCQ7-TX	TOUR X-STIFF	46"	76g	.335"	3.0"	.606"	3.2°	LOW/MID
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD CQ 8 X	WCQ8-X	X-STIFF	46"	83g	.335"	3.0"	.604"	3.0°	LOW/MID

Tip Trimming for Standard Bore Heads: Driver: 0.0", #3 wood: .5", #5 Wood or greater 1.0", then Butt Cut to desired club length after assembly.



PROSCHOICEGOLFSHAFTS.COM