



The Graphite Design **Tour AD VF** – **Victory Force** was designed and is manufactured at the Graphite Design Japan factory headquarters and are jet black with red accents and finished with a gloss clear coat.

The **Tour AD VF**, like the other high performance Tour AD wood shafts, utilizes premium, aerospace quality carbon-fiber materials and are available in 40g R2, R1 and S flex, 50g R2, R1, S and X flex, 60g SR, S, X and TX flex, 70g S, X and TX flex and 80g X flex.

The **Tour AD VF** shaft profile is Firm in the butt section, Stiff+ in the center section and has a Very Stiff tip to promote Low/Mid launch angles and Low-ball spin rates. The **Tour AD VF** shafts utilizes the modern **TORAYCA® M40X** carbon-fiber material in the butt section of the shaft to support a stiff, yet smooth feeling kick point and the ultra-high modulus **TORAYCA® T1100G** carbon-fiber material in the middle thru to the tip section of the shaft for unrivaled shaft stability and precise ball control without the loss of the exceptional feel that Graphite Design shafts are so well known for.

Victories require Force. Visit your local Graphite Design dealer for a fitting and experience the **Tour AD VF**, where you will discover the Force necessary to achieve Victory.

MSRP \$500

PROSCHOICEGOLFSHAFTS.COM

760-476-9598



**Pro's Choice**  
EXCLUSIVE DISTRIBUTOR FOR GRAPHITE DESIGN

## SHAFT SPECIFICATIONS

Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD VF 4 R2	WVF4-R2	LITE/SENIOR	46"	46g	.335"	3.0"	.594"	5.5°	MID/HIGH
TOUR AD VF 4 R1	WVF4-R1	REGULAR	46"	46g	.335"	3.0"	.594"	5.5°	MID/HIGH
TOUR AD VF 4 S	WVF4-S	STIFF	46"	47g	.335"	3.0"	.596"	5.6°	MID/HIGH
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD VF 5 R2	WVF5-R2	LITE/SENIOR	46"	55g	.335"	3.0"	.596"	4.3°	MID/HIGH
TOUR AD VF 5 R1	WVF5-R1	REGULAR	46"	55g	.335"	3.0"	.596"	4.3°	MID/HIGH
TOUR AD VF 5 S	WVF5-S	STIFF	46"	56.5g	.335"	3.0"	.598"	4.3°	MID/HIGH
TOUR AD VF 5 X	WVF5-X	X-STIFF	46"	59g	.335"	3.0"	.602"	4.3°	MID/HIGH
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD VF 6 SR	WVF6-SR	STIFF REGULAR	46"	64g	.335"	3.0"	.600"	3.3°	MID/HIGH
TOUR AD VF 6 S	WVF6-S	STIFF	46"	66.5g	.335"	3.0"	.602"	3.3°	MID/HIGH
TOUR AD VF 6 X	WVF6-X	X-STIFF	46"	67g	.335"	3.0"	.604"	3.3°	MID/HIGH
TOUR AD VF 6 TX	WVF6-TX	TOUR X-STIFF	46"	68.5g	.335"	3.0"	.606"	3.3°	MID/HIGH
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD VF 7 S	WVF7-S	STIFF	46"	74g	.335"	3.0"	.602"	3.0°	MID/HIGH
TOUR AD VF 7 X	WVF7-X	X-STIFF	46"	75.5g	.335"	3.0"	.604"	3.0°	MID/HIGH
TOUR AD VF 7 TX	WVF7-TX	TOUR X-STIFF	46"	77g	.335"	3.0"	.606"	3.0°	MID/HIGH
Shaft Type	Part Number	Flex	Length	Wt	Tip OD	Tip Para.	Butt OD	Torque	Kick pt
TOUR AD VF 8 X	WVF8-X	X-STIFF	46"	85g	.335"	3.0"	.608"	2.8°	MID/HIGH

Tip Trimming for Standard Bore Heads: Driver: 0.0", #3 wood: .5", #5 Wood or greater 1.0", then Butt Cut to desired club length after assembly.



PROSCHOICEGOLFSHAFTS.COM